


KS1

KOLORMAX KS1, the selection of lightweight, low-carbon environmental protection design, the weight of the whole fixture is only 1.7kg, green lighting energy consumption ratio of 670lm/kg, the use of high efficiency and 4-in-1 RGBL LED chip, to ensure that the LED in high-intensity operation stable as a rock, durable, unique high color mixing design, easy to handle multi-color output color mixing. The IP67 level protection, easy to cope with outdoor environment. Suitable for lawn wetlands, parks and other outdoor environment. KOLORMAX KS1, small body large energy, landscape lighting perfect option.



TECHNICAL PARAMETER

Product code: AM1421KXLET

Max. Power: 40W

Light source: 4 in 1 RGBL

Luminous Flux: 1809lm

Peak Intensity: 8500cd(15°)

CRI: Ra: 85

CTO: 1800K-10000K

Built-in colors: 24 preset colors

Con Personality: DMX512, RDM

Operating voltage: AC220V-50/60Hz


Working Temperature: -20°C~45°C

Protection Level: IP67

Dimensions (L*W*H): 179*127*177mm

weight: 1.7kg


ANGLE




SPECIFICATIONS




DIMENSIONAL DRAWING




LIGHT DISTRIBUTION DIAGRAM (* THE ABOVE COLOR TEMPERATURES ARE ACHIEVED BY YAJIANG DIGITAL COLOR TECHNOLOGY AND CCS TECHNOLOGY)




Lumen	1809lm
Illuminance	339lx(5m)
Peak Intensity	8500cd(15°)




Lumen	1634lm
Illuminance	258lx(5m)
Peak Intensity	6467cd(15°)




Lumen	1675lm
Illuminance	280lx(5m)
Peak Intensity	7023cd(15°)



Lumen	1681lm
Illuminance	278lx(5m)
Peak Intensity	6990cd(15°)



Lumen	1657lm
Illuminance	276lx(5m)
Peak Intensity	6925cd(15°)



Lumen	1680lm
Illuminance	276lx(5m)
Peak Intensity	6923cd(15°)

ILLUMINANCE AT DISTANCE

